9.47% Per-Watt Low Light Power Gain: Empirical Result of a Residential Rooftop PV System in Jiangsu

Recently, Jinko Solar conducted a comparative test on the power generation of each string in an existing residential PV project in Northern Jiangsu Province. Based on the measured power generation data from September 1 to November 9, 2025, the results show that the single-watt power generation performance of Jinko Solar Tiger Neo Series modules was significantly superior to that of N-type BC modules with the same power during the test period. The empirical results fully demonstrate that Jinko Solar Tiger Neo Series modules have stronger environmental adaptability and power generation efficiency in residential PV scenarios, especially under complex lighting conditions in autumn and winter.

Icw Amlajsqgmlq8

/,Bspgle rfc rcqr ncpgmb* rfc rmr_j qglejc+u_rr nmucp ec lcp_rgml md Hgl im Qmj_p Rgecp Lcm kmbsjcq pc_afcb 062,12 iUf-iU* ufgjc rf_r md L+rwnc @A kmbsjcq ugrf rfc q_kc nmucp u_q 055,40 iUf-iU, Rfc Rgecp Lcm Qcpgcq _afgctcb _ rmr_j qglejc+u_rr e_gl md **0,20 #** * bckmlqrp_rgle pck_pi_`jc_bt_lr_ecqgl nmucp ec lcp_rgml ncpdmpk_lac,



0,Dpmk _ rgkc+qcekclr ncpqncargtc* rfc Rgecp Lcm kmbsjcq cvfg`gr bgqrglar ncpdmpk_lac bg cpclrg_rgml* ugrf n_prgasj_pjw qgelg a_lre_glq bspgle rfc kmplgle _lb ctclgle jmu+gpp_bg_rgml ncpgmbq, Rfc qglejc+u_rr e_gl pc_afcq **5,72 #** dpmk 4 ?K rm 5 ?K _lb _q fgef _q **7,25 #** dpmk 4 NK rm 5 NK* bckmlqrp_rgle cvacjjclr _b_nr_`gjgrw gl jmu+jgefrcltgpmlkclrq,



Npmhcar @_aiepmslb8

The current residential PV market has higher requirements for the power generation efficiency, stability, and full-scenario adaptability of modules. To objectively evaluate the practical application performance of Jinko Solar Tiger Neo Series modules, Jinko Solar selected an existing residential PV project in Northern Jiangsu Province for comparative empirical testing. The test results provide important reference value for module selection, system optimization, and investment return evaluation of residential PV projects.

Npmhcar Bcqgel8

This field test is located at a residential PV station in Northern Jiangsu Province. The test period is set from September 1 to November 9, 2025, covering typical lighting periods in autumn and winter to ensure that the collected data can fully reflect the real power generation performance of the modules under the lighting conditions of this season. To eliminate the interference of installation condition differences on the test results, the module installation inclination angle is uniformly set to 20 °, ensuring consistent basic conditions for light reception of the two types of test modules. The test samples are selected following the principle of equivalence, with 16 Jinko Solar Tiger Neo Series modules and 16 N-type BC modules of the same power (rated power: 635W) configured respectively. This design aims to deeply explore the differences in power generation performance between the two types of modules under different light intensities and time periods, providing comprehensive and accurate data support for the analysis of gain causes.



E_gl ?l_jwqgq8

/,Qgelg a_lr ?bt_lr_ecq gl Jmu+Gpp_bg_rgml Ncpdmpk_lac8 N-type BC modules adopt a backside finger-crossed electrode structure, and their patterning process requires multiple grooving operations, which inevitably form a large number of leakage current sites. Such structural defects have a particularly prominent negative impact on power generation performance under low-irradiation environments, leading to significant power generation losses. In contrast, Jinko Solar Tiger Neo Series modules effectively reduce the generation of leakage current through optimized electrode structure design, maintaining stable and efficient power generation even during the morning and evening low-light periods, thus achieving significant gains.

0,Dsjj Srgjgx_rgml md Fgef @gd_ag_jgrw8 The test period covers the autumn and winter seasons, during which the proportion of air-scattered light and ground-reflected light received by the backside of the modules in the total light resources is significantly higher than that in summer. Jinko Solar Tiger Neo Series modules have the advantage of high bifaciality, enabling them to fully capture diverse light resources and convert them into electrical energy. Compared with competing modules with limited single-sided power generation performance, their technical advantages are further amplified under the lighting conditions of autumn and winter, contributing to the improvement of overall power generation.